acrojack mini | short

We aim to create cleaner ceilings.
Show what you want, hide what you need.



© Prado Europe bv
We reserve the right to change technical details without notice if the product's appearance or functionality is unaffected.

luminaire specs 3

finishes 5


luminaire output 6

accessories & drivers 8

installation rings 9

© Prado Europe bv We reserve the right to change technical details without notice if the product's appearance or functionality is unaffected.





acrojack mini | short

installation

luminaire specs

delivered lumen	up to 725lm			
watts	up to 8.9W			
efficacy	up to 101lm/W			
lamp	LED			
optics	10° pc	20° pc	40° pc	60° pc
	40° glass			
	honeycomb available for all pc lenses			
	ellipitical lens available only for 20° pc			
driver	excluded			
IP	IP20			
CRI/Ra	CRI 90+		CRI 97	
R9 value	CRI 90+: >50		CRI 97: >91	
color temperature (CCT)	2400K*	2700K	3000K	3500K*
	4000K*	dim to warm: 3000K > 1800K**		
	* only available in CRI 97			
	** only available in CRI 90+			
color consistency	SDCM2			
class	III			
recess height	47 mm			
installation depth	driver remote: 47 mm			
adjustability	rotation 360°		tilt 90°	

location	indoor	
energy class	F	
marking	CE	
L80	>55000 h	
installation rings (not incl.)	plaster ring jack	↗
	clt ring jack	↗
aluminum finishes	black ano	white struc
	brushed steel	brushed grey
	brushed bronze	
aluminum weight	0.21 kg	
brass finishes	brushed nickel	light bronze
	dark bronze	canon de fusil dark
	canon de fusil light	
brass weight	0.38 kg	
warranty	2 years (5 years on LED)	↗


Respect distances, cable sections and IP ratings.
Split AC and DC to prevent LED glowing.

© Prado Europe bv

extension parts

extension length	total length (L)
100 mm	123 mm
200 mm	223 mm
300 mm	323 mm

Combining extension parts is possible up to 1 m.



© Prado Europe bv We reserve the right to change technical details without notice if the product's appearance or functionality is unaffected.

finishes

aluminum finishes

white struc (RAL 9003)



brushed steel



brushed bronze



brushed grey



black ano



brass finishes

brushed nickel



light bronze



dark bronze



canon de fusil light




canon de fusil dark




Custom RAL and brass finishes available on request.

correlated color temperature (CCT)


2400K: candle white




2700K: extra warm white




3000K: warm white




3500K: neutral white



4000K: cool white



dim to warm: 3000K > 1800K




max. mA

	10° pc	20° pc	40° pc	60° pc	40° glass	dim to warm (40° glass)
aluminum	350mA max	350mA max	350mA max	350mA max	500mA max	350mA max
brass	350mA max	350mA max	350mA max	350mA max	500mA max	350mA max


luminaire output

		350mA			500mA
		(6.6W, 19.9Vf)	(6.4W, 18.3Vf)	(6.0W, 17.1Vf)	(8.9W, 17.8Vf)
2400K	10° pc	425lm	-	-	-
	20° pc	-	500lm	-	-
	40° pc	-	500lm	-	-
	60° pc	-	450lm	-	-
	40° glass	-	-	425lm	575lm
2700K	10° pc	475lm	-	-	-
	20° pc	-	550lm	-	-
	40° pc	-	550lm	-	-
	60° pc	-	500lm	-	-
	40° glass	-	-	475lm	650lm
3000K	10° pc	500lm	-	-	-
	20° pc	-	575lm	-	-
	40° pc	-	575lm	-	-
	60° pc	-	525lm	-	-
	40° glass	-	-	500lm	675lm
3500K	10° pc	525lm	-	-	-
	20° pc	-	600lm	-	-
	40° pc	-	600lm	-	-
	60° pc	-	550lm	-	-
	40° glass	-	-	525lm	700lm
4000K	10° pc	550lm	-	-	-
	20° pc	-	625lm	-	-
	40° pc	-	625lm	-	-
	60° pc	-	575lm	-	-
	40° glass	-	-	550lm	725lm
dim to warm	40° glass	-	-	425lm	-


© Prado Europe bv We reserve the right to change technical details without notice if the product's appearance or functionality is unaffected.




10° pc




20° pc




40° pc




60° pc



40° glass



dim to warm (40° glass)



© Prado Europe bv We reserve the right to change technical details without notice if the product's appearance or functionality is unaffected.

accessories

trimless installation rings (not incl.)

	application	drill hole	product code	spec sheet
plaster ring jack	plastered ceiling	Ø76 mm	8000-0006	↗
clt ring jack	CLT	consult installation	8000-0016	↗

drivers (not incl.)

	number of fixtures	IP rating	product code	installation
DALI dimmable driver 38W constant current multi power	1-2 fx	IP20	8000-0021	remote only
1-10V dimmable driver 36W constant current multi power	1-2 fx	IP20	8000-0022	remote only
non-dimmable driver 42W constant current multi power	1-2 fx	IP20	8000-0023	remote only
CASAMBI dimmable driver 38W constant current multi power	1-2 fx	IP20	8000-0028	remote only
DALI dimmable driver mini slim 15W constant current NFC 350mA	1 fx	IP20	8000-0060	remote only
DALI dimmable driver mini slim 15W constant current NFC 500mA	1 fx	IP20	8000-0065	remote only
DALI / 0-10V dimmable driver 60W constant current multi power	2-5 fx	IP20	8000-0026	remote only
DALI deep dim driver 20W constant current 350mA	1-2 fx	IP20	8000-0031	remote only
DALI deep dim driver 20W constant current 500mA	1-2 fx	IP20	8000-0030	remote only
DALI dimmable power converter 48V to 350-700mA	1-2 fx	IP20	8000-0037	remote only
TRIAC dimmable driver 7W constant current 350mA	1 fx	IP20	8000-0034	remote only
TRIAC dimmable driver 10W constant current 500mA	1 fx	IP20	8000-0035	remote only
TRIAC dimmable driver mini 10W constant current 350mA	1 fx	IP20	8000-0043	remote only
TRIAC dimmable driver mini 10W constant current 500mA	1 fx	IP20	8000-0044	remote only


driver matrix

© Prado Europe bv We reserve the right to change technical details without notice if the product's appearance or functionality is unaffected.

trimless installation rings (not incl.)

	application	drill hole	product code	spec sheet
plaster ring jack	plastered ceiling	Ø76 mm	8000-0006	↗
clt ring jack	CLT	consult installation	8000-0016	↗


plastered ceiling



plaster ring jack

installation

location	ceiling indoor - non-sloped only	
plaster thickness	3.6 mm	
drill hole	Ø76 mm	
installation depth	47 mm	
trimless tool (not incl.)	Ø38 / Ø57 / jack	8000-0098



clt ring jack


installation

location	ceiling indoor - non-sloped only
clt ring height	36 mm
drill hole	consult installation

© Prado Europe bv
We reserve the right to change technical details without notice if the product's appearance or functionality is unaffected.


free air dimensions (l x w)

	remote driver
350mA	100 x 100 mm
500mA	150 x 150 mm



wiring diagram

serial connection



driver connections

© Prado Europe bv
We reserve the right to change technical details without notice if the product's appearance or functionality is unaffected.