light only | short

We aim to create cleaner ceilings.
Show what you want, hide what you need.



© Prado Europe bv
We reserve the right to change technical details without notice if the product's appearance or functionality is unaffected.

luminaire specs 3

finishes 4

luminaire output 5


accessories 7

installation rings 8

drivers 10

© Prado Europe bv We reserve the right to change technical details without notice if the product's appearance or functionality is unaffected.





light only | short

installation

luminaire specs

delivered lumen	up to 850lm			
watts	up to 8.9W			
efficacy	up to 105lm/W			
lamp	LED			
optics	25° glass	40° glass	60° glass	
driver	excluded			
IP	IP44			
CRI/Ra	CRI 90+		CRI 97	
R9 value	CRI 90+: >50		CRI 97: >91	
color temperature (CCT)	2400K*	2700K	3000K	3500K*
	4000K*	dim to warm: 3000K > 1800K**		
	* only available in CRI 97			
	** only available in CRI 90+			
color consistency	SDCM2			
class	III			
recess height	74 mm			
installation depth	driver remote: 79 mm			
	local driver : consult driver specs ↗			
adjustability	rotation 360°		tilt 45°	
location	indoor			
energy class	F			

marking	CE	
L80	>55000 h	
installation rings (not incl.)	plaster ring Ø108 ↗	
	adj. thick plaster ring Ø108 ↗	
	clt csc ring Ø108 ↗	
	concrete ring + cap Ø108 ↗	
aluminum finishes	black ano	white struc
	brushed steel	brushed grey
	brushed bronze	
aluminum weight	0.66 kg	
brass finishes	brushed nickel	light bronze
	dark bronze	canon de fusil dark
	canon de fusil light	
brass weight	1.20 kg	
warranty	2 years (5 years on LED) ↗	

Respect distances, cable sections and IP ratings.
Split AC and DC to prevent LED glowing.

© Prado Europe bv We reserve the right to change technical details without notice if the product's appearance or functionality is unaffected.

finishes

aluminum finishes

white struc (RAL 9003)



brushed steel



brushed bronze



brushed grey



black ano



brass finishes

brushed nickel



light bronze



dark bronze



canon de fusil light




canon de fusil dark




Custom RAL and brass finishes available on request.

correlated color temperature (CCT)


2400K: candle white




2700K: extra warm white




3000K: warm white




3500K: neutral white



4000K: cool white



dim to warm: 3000K > 1800K



© Prado Europe bv

We reserve the right to change technical details without notice if the product's appearance or functionality is unaffected.


max. mA

	25° glass	40° glass	60° glass	dim to warm (25° glass)	dim to warm (40° glass)
aluminum	500mA max	500mA max	500mA max	350mA max	350mA max
brass	500mA max	500mA max	500mA max	350mA max	350mA max


luminaire output

		350mA	500mA
		(6.0W, 17.1Vf)	(8.9W, 17.8Vf)
2400K	25° glass	400lm	550lm
	40° glass	500lm	650lm
	60° glass	525lm	675lm
2700K	25° glass	450lm	625lm
	40° glass	550lm	750lm
	60° glass	575lm	775lm
3000K	25° glass	475lm	650lm
	40° glass	575lm	775lm
	60° glass	600lm	800lm
3500K	25° glass	500lm	675lm
	40° glass	600lm	800lm
	60° glass	625lm	850lm
4000K	25° glass	525lm	700lm
	40° glass	625lm	825lm
	60° glass	650lm	850lm
dim to warm	25° glass	425lm	-
	40° glass	575lm	-


© Prado Europe bv We reserve the right to change technical details without notice if the product's appearance or functionality is unaffected.




25° glass




40° glass




60° glass



dim to warm (25° glass)



dim to warm (40° glass)



© Prado Europe bv
We reserve the right to change technical details without notice if the product's appearance or functionality is unaffected.

accessories

trimless installation rings (not incl.)

	application	drill hole	product code	spec sheet
plaster ring Ø108	plastered ceiling	Ø132 mm	8000-0001	↗
adj. thick plaster ring Ø108 (12 - 33 mm)	plastered ceiling	Ø132 mm	8000-0101	↗
clt csc ring Ø108 (before claring ceiling)	CLT / CSC	consult installation	8000-0011	↗
concrete ring + cap Ø108	concrete ceiling	consult installation	8000-0111	↗

drivers (not incl.)

	number of fixtures	IP rating	product code
DALI dimmable driver 38W constant current multi power	1-2 fx	IP20	8000-0021
1-10V dimmable driver 36W constant current multi power	1-2 fx	IP20	8000-0022
non-dimmable driver 42W constant current multi power	1-2 fx	IP20	8000-0023
CASAMBI dimmable driver 38W constant current multi power	1-2 fx	IP20	8000-0028
DALI dimmable driver mini slim 15W constant current NFC 350mA	1 fx	IP20	8000-0060
DALI dimmable driver mini slim 15W constant current NFC 500mA	1 fx	IP20	8000-0065
DALI / 0-10V dimmable driver 60W constant current multi power	2-5 fx	IP20	8000-0026
DALI deep dim driver 20W constant current 350mA	1-2 fx	IP20	8000-0031
DALI deep dim driver 20W constant current 500mA	1-2 fx	IP20	8000-0030
DALI dimmable power converter 48V to 350-700mA	1-2 fx	IP20	8000-0037
TRIAC dimmable driver 7W constant current 350mA	1 fx	IP20	8000-0034
TRIAC dimmable driver 10W constant current 500mA	1 fx	IP20	8000-0035
TRIAC dimmable driver mini 10W constant current 350mA	1 fx	IP20	8000-0043
TRIAC dimmable driver mini 10W constant current 500mA	1 fx	IP20	8000-0044

installation depths


driver matrix

© Prado Europe bv We reserve the right to change technical details without notice if the product's appearance or functionality is unaffected.

trimless installation rings (not incl.)

	application	drill hole	product code	spec sheet
plaster ring Ø108	plastered ceiling	Ø132 mm	8000-0001	↗
adj. thick plaster ring Ø108 (12 - 33 mm)	plastered ceiling	Ø132 mm	8000-0101	↗
clt csc ring Ø108 (before claring ceiling)	CLT / CSC	consult installation	8000-0011	↗
concrete ring + cap Ø108	concrete ceiling	consult installation	8000-0111	↗


plastered ceiling



plaster ring Ø108

installation

location	ceiling indoor	
plaster thickness	3.6 mm	
drill hole	Ø132 mm - h 85 mm	
installation depth	79 mm	
trimless tool (not incl.)	Ø108	8000-0097




adj. thick plaster ring Ø108

installation

location	ceiling indoor	
plaster thickness	min. 12 mm	max. 33 mm
drill hole	Ø132 mm - h 80 mm	
installation depth	79 mm	
trimless tool (not incl.)	Ø108	8000-0097

© Prado Europe bv We reserve the right to change technical details without notice if the product's appearance or functionality is unaffected.

clt csc ceiling




clt csc ring ∅108

installation

location	ceiling indoor - non-sloped only
cut-out	consult installation

concrete ceiling



concrete ring + cap ∅108

installation


location	ceiling indoor
cut-out	consult installation

© Prado Europe bv We reserve the right to change technical details without notice if the product's appearance or functionality is unaffected.

drivers installation depth

	installation rings Ø108	concrete ring + cap Ø108
DALI dimmable driver 38W constant current multi power	150 mm / remote	remote
1-10V dimmable driver 36W constant current multi power	130 mm / remote	remote
non-dimmable driver 42W constant current multi power	150 mm / remote	remote
CASAMBI dimmable driver 38W constant current multi power	150 mm / remote	remote
DALI dimmable driver mini slim 15W constant current NFC 350mA	140 mm / remote	remote
DALI dimmable driver mini slim 15W constant current NFC 500mA	140 mm / remote	remote
DALI / 0-10V dimmable driver 60W constant current multi power	remote	remote
DALI deep dim driver 20W constant current 350mA	120 mm / remote	remote
DALI deep dim driver 20W constant current 500mA	120 mm / remote	remote
DALI dimmable power converter 48V to 350-700mA	90 mm / remote	remote
TRIAC dimmable driver 7W constant current 350mA	130 mm / remote	remote
TRIAC dimmable driver 10W constant current 500mA	130 mm / remote	remote
TRIAC dimmable driver mini 10W constant current 350mA	60 mm	/
TRIAC dimmable driver mini 10W constant current 500mA	60 mm	/

driver matrix




© Prado Europe bv
We reserve the right to change technical details without notice if the product's appearance or functionality is unaffected.


free air dimensions (l x w)

	remote driver	local driver
350mA	150 x 150 mm	250 x 250 mm
500mA	150 x 150 mm	250 x 250 mm

remote driver




local driver



© Prado Europe bv
We reserve the right to change technical details without notice if the product's appearance or functionality is unaffected.

wiring diagram

serial connection



driver connections

© Prado Europe bv
We reserve the right to change technical details without notice if the product's appearance or functionality is unaffected.