
trim spot | short

We aim to create cleaner ceilings.
Show what you want, hide what you need.



© Prado Europe bv
We reserve the right to change technical details without notice if the product's appearance or functionality is unaffected.

luminaire specs 3


finishes 4


luminaire output 5

drivers 7

fixation 8

© Prado Europe bv We reserve the right to change technical details without notice if the product's appearance or functionality is unaffected.





trim spot | short

installation

luminaire specs

delivered lumen	up to 725lm	
watts	up to 8.9W	
efficacy	up to 86lm/W	
lamp	LED	
optics	25° glass 40° glass 60° glass	
driver	excluded	
IP	IP44 (60° glass)	
	IP65 (25°, 40° glass)	
CRI/Ra	CRI 90+	CRI 97
R9 value	CRI 90+: >50	CRI 97: >91
color temperature (CCT)	2400K* 2700K 3000K 3500K*	
	4000K* dim to warm: 3000K > 1800K**	
	* only available in CRI 97	
	** only available in CRI 90+	
color consistency	SDCM2	
class	III	
drill hole size	Ø68 mm	
ceiling thickness	min. 2 mm	max. 24 mm
recess height	64 mm	
installation depth	driver remote: 69 mm	
	local driver: consult driver specs ↗	
location	indoor	

energy class	F	
marking	CE	
L80	>55000 h	
fixation	single springs →	
	double springs →	
aluminum finishes	black ano	white struc
	brushed steel	brushed grey
	brushed bronze	
aluminum weight	0.37 kg	
brass finishes	brushed nickel	light bronze
	dark bronze	canon de fusil dark
	canon de fusil light	
brass weight	0.37 kg	
warranty	2 years (5 years on LED) ↗	

Respect distances, cable sections and IP ratings.
Split AC and DC to prevent LED glowing.

© Prado Europe bv
We reserve the right to change technical details without notice if the product's appearance or functionality is unaffected.

finishes

aluminum finishes

white struc (RAL 9003)



brushed steel



brushed bronze



brushed grey



black ano



brass finishes

brushed nickel



light bronze



dark bronze



canon de fusil light




canon de fusil dark




Custom RAL and brass finishes available on request.

correlated color temperature (CCT)


2400K: candle white




2700K: extra warm white




3000K: warm white




3500K: neutral white



4000K: cool white



dim to warm: 3000K > 1800K




max. mA

	25° glass	40° glass	60° glass	dim to warm (25° glass)	dim to warm (40° glass)
aluminum	500mA max	500mA max	500mA max	350mA max	350mA max
brass	500mA max	500mA max	500mA max	350mA max	350mA max


luminaire output

		350mA	500mA
		(6.0W, 17.1Vf)	(8.9W, 17.8Vf)
2400K	25° glass	350lm	500lm
	40° glass	425lm	575lm
	60° glass	400lm	550lm
2700K	25° glass	375lm	550lm
	40° glass	475lm	650lm
	60° glass	450lm	625lm
3000K	25° glass	400lm	575lm
	40° glass	500lm	675lm
	60° glass	475lm	650lm
3500K	25° glass	425lm	600lm
	40° glass	525lm	700lm
	60° glass	500lm	675lm
4000K	25° glass	550lm	725lm
	40° glass	550lm	725lm
	60° glass	525lm	700lm
dim to warm	25° glass	425lm	-
	40° glass	525lm	-


© Prado Europe bv We reserve the right to change technical details without notice if the product's appearance or functionality is unaffected.




25° glass




40° glass




60° glass



dim to warm (25° glass)




dim to warm (40° glass)



© Prado Europe bv

drivers (not incl.)	number of fixtures	IP rating	product code	installation depth
DALI dimmable driver 38W constant current multi power	1-2 fx	IP20	8000-0021	80 mm / remote
1-10V dimmable driver 36W constant current multi power	1-2 fx	IP20	8000-0022	70 mm / remote
non-dimmable driver 42W constant current multi power	1-2 fx	IP20	8000-0023	80 mm / remote
CASAMBI dimmable driver 38W constant current multi power	1-2 fx	IP20	8000-0028	80 mm / remote
DALI dimmable driver mini slim 15W constant current NFC 350mA	1 fx	IP20	8000-0060	60 mm / remote
DALI dimmable driver mini slim 15W constant current NFC 500mA	1 fx	IP20	8000-0065	60 mm / remote
DALI / 0-10V dimmable driver 60W constant current multi power	2-5 fx	IP20	8000-0026	remote
DALI deep dim driver 20W constant current 350mA	1-2 fx	IP20	8000-0031	60 mm / remote
DALI deep dim driver 20W constant current 500mA	1-2 fx	IP20	8000-0030	60 mm / remote
DALI dimmable power converter 48V to 350-700mA	1-2 fx	IP20	8000-0037	30 mm / remote
TRIAC dimmable driver 7W constant current 350mA	1 fx	IP20	8000-0034	60 mm / remote
TRIAC dimmable driver 10W constant current 500mA	1 fx	IP20	8000-0035	60 mm / remote
TRIAC dimmable driver mini 10W constant current 350mA	1 fx	IP20	8000-0043	40 mm
TRIAC dimmable driver mini 10W constant current 500mA	1 fx	IP20	8000-0044	40 mm

driver matrix





© Prado Europe bv We reserve the right to change technical details without notice if the product's appearance or functionality is unaffected.

fixation

	product code	ceiling thickness
single springs - 10 pack (5 sets)	8001-9689	min. 2 mm - max. 24 mm
double springs - 10 pack (5 sets)	8000-8480	min. 24 mm

replacing single springs to double springs (use a T6 torx screwdriver)







free air dimensions (l x w)

	remote driver	local driver
350mA	100 x 100 mm	200 x 200 mm
500mA	150 x 150 mm	200 x 200 mm

remote driver




local driver



© Prado Europe bv

wiring diagram

serial connection



driver connections

© Prado Europe bv We reserve the right to change technical details without notice if the product's appearance or functionality is unaffected.