
trim spot mini | short

We aim to create cleaner ceilings.
Show what you want, hide what you need.



© Prado Europe bv
We reserve the right to change technical details without notice if the product's appearance or functionality is unaffected.

luminaire specs 3


finishes 4


luminaire output 5

drivers 7

fixation 8

© Prado Europe bv We reserve the right to change technical details without notice if the product's appearance or functionality is unaffected.





trim spot mini | short

installation

luminaire specs

delivered lumen	up to 725lm			
watts	up to 8.9W			
efficacy	up to 94lm/W			
lamp	LED			
optics	20° pc	40° pc	60° pc	40° glass
driver	excluded			
IP	IP20 (20°, 40°, 60° pc)			
	IP65 (40° glass)			
CRI/Ra	CRI 90+		CRI 97	
R9 value	CRI 90+: >50		CRI 97: >91	
color temperature (CCT)	2400K*	2700K	3000K	3500K*
	4000K*	dim to warm: 3000K > 1800K**		
	* only available in CRI 97			
	** only available in CRI 90+			
color consistency	SDCM2			
class	III			
drill hole size	Ø40 mm			
ceiling thickness	min. 2 mm		max. 24 mm	
recess height	62 mm			
installation depth	driver remote: 67 mm			
	local driver: consult driver specs ↗			
location	indoor			

energy class	F	
marking	CE	
L80	>55000 h	
fixation	single springs →	
	double springs →	
aluminum finishes	black ano	white struc
	brushed steel	brushed grey
	brushed bronze	
aluminum weight	0.16 kg	
brass finishes	brushed nickel	light bronze
	dark bronze	canon de fusil dark
	canon de fusil light	
brass weight	0.25 kg	
warranty	2 years (5 years on LED) ↗	

Respect distances, cable sections and IP ratings.
Split AC and DC to prevent LED glowing.

© Prado Europe bv
We reserve the right to change technical details without notice if the product's appearance or functionality is unaffected.

finishes

aluminum finishes

white struc (RAL 9003)



brushed steel



brushed bronze



brushed grey



black ano



brass finishes

brushed nickel



light bronze



dark bronze



canon de fusil light




canon de fusil dark




Custom RAL and brass finishes available on request.

correlated color temperature (CCT)


2400K: candle white




2700K: extra warm white




3000K: warm white




3500K: neutral white



4000K: cool white



dim to warm: 3000K > 1800K




max. mA

	20° pc	40° pc	60° pc	40° glass	dim to warm (40° glass)
aluminum	350mA max	350mA max	350mA max	350mA max	350mA max
brass	350mA max	350mA max	350mA max	350mA max	350mA max


luminaire output

		350mA		500mA
		(6.4W, 18.3Vf)	(6.0W, 17.1Vf)	(8.9W, 17.8Vf)
2400K	20° pc	500lm	-	-
	40° pc	500lm	-	-
	60° pc	450lm	-	-
	40° glass	-	425lm	575lm
2700K	20° pc	550lm	-	-
	40° pc	550lm	-	-
	60° pc	500lm	-	-
	40° glass	-	475lm	650lm
3000K	20° pc	575lm	-	-
	40° pc	575lm	-	-
	60° pc	525lm	-	-
	40° glass	-	500lm	675lm
3500K	20° pc	600lm	-	-
	40° pc	600lm	-	-
	60° pc	550lm	-	-
	40° glass	-	525lm	700lm
4000K	20° pc	625lm	-	-
	40° pc	625lm	-	-
	60° pc	575lm	-	-
	40° glass	-	550lm	725lm
dim to warm	40° glass	-	425lm	-


© Prado Europe bv We reserve the right to change technical details without notice if the product's appearance or functionality is unaffected.




20° pc




40° pc




60° pc



40° glass




dim to warm (40° glass)



drivers (not incl.)	number of fixtures	IP rating	product code	installation depth
DALI dimmable driver 38W constant current multi power	1-2 fx	IP20	8000-0021	remote only
1-10V dimmable driver 36W constant current multi power	1-2 fx	IP20	8000-0022	remote only
non-dimmable driver 42W constant current multi power	1-2 fx	IP20	8000-0023	remote only
CASAMBI dimmable driver 38W constant current multi power	1-2 fx	IP20	8000-0028	remote only
DALI dimmable driver mini slim 15W constant current NFC 350mA	1 fx	IP20	8000-0060	remote only
DALI / 0-10V dimmable driver 60W constant current multi power	2-5 fx	IP20	8000-0026	remote only
DALI deep dim driver 20W constant current 350mA	1-2 fx	IP20	8000-0031	remote only
DALI dimmable power converter 48V to 350-700mA	1-2 fx	IP20	8000-0037	50 mm / remote
TRIAC dimmable driver 7W constant current 350mA	1 fx	IP20	8000-0034	remote only
TRIAC dimmable driver mini 10W constant current 350mA	1 fx	IP20	8000-0043	45 mm / remote

driver matrix





© Prado Europe bv We reserve the right to change technical details without notice if the product's appearance or functionality is unaffected.

fixation

	product code	ceiling thickness
single springs mini - 10 pack (5 sets)	8001-9690	min. 2 mm - max. 24 mm
double springs mini - 10 pack (5 sets)	8000-9656	min. 24 mm

use a Phillips screwdriver to replace the springs







free air dimensions (l x w)

	remote driver	local driver
350mA	100 x 100 mm	200 x 200 mm

remote driver




local driver



wiring diagram

serial connection



driver connections

© Prado Europe bv We reserve the right to change technical details without notice if the product's appearance or functionality is unaffected.