




installation

trimless spot adjustable 2.0

light specs

lamp	LED	
optic	lens	
driver	excluded	
suitable for	damp locations	
CRI	90+	97
SDCM	SDCM2	
class	class 2	
recess height	2-7/8"	
location	indoor	
marking	UL (E543420)	

accessories

installation	product code
mud ring 2-1/4"	9001-0003
mud ring adj. 2-1/4"	9001-0123
clt csc ring 2-1/4"	9001-0013
concrete ring + cap 2-1/4"	9001-0113

IC boxes	
IC box + plaster frame 3-1/2" high	9000-0101
bar hanger kit	9000-0102

trimless spot adjustable 2.0

luminaire output

	2700K				3000K			
	10°	20°	40°	60°	10°	20°	40°	60°
350mA (5.7W)	-	525lm	525lm	525lm	-	550lm	550lm	550lm
500mA (10W)	-	-	710lm	-	-	-	750lm	-

accessories

drivers (for remote installation or in IC box 3-1/2" high)	product code
SOLOdrive 0-10V 350mA 22W (1-2fx)	9000-1008
SOLOdrive 0-10V 500mA 22W (1-2fx)	9000-1002
SOLOdrive DALI 350mA 22W (1-2fx)	9000-1006
SOLOdrive DALI 500mA 22W (1-2fx)	9000-1001
Hatch phase dimming drive constant current 350mA - 12W (1fx)	9000-1003
Hatch phase dimming drive constant current 500mA - 12W (1fx)	9000-1004
drivers (for remote installation only)	
Hatch phase dimming drive constant current 350mA - 30W (2-3fx)	9000-1010
Hatch phase dimming drive constant current 500mA - 30W (2-3fx)	9000-1011