



installation

acrobat mini short

light specs

lamp	LED	
optic	lens	
driver	excluded	
Suitable for	dry locations	
CRI	90+	97
SDCM	SDCM2	
class	class 2	
recess height	1-3/4"	
tilt	60°	
location	indoor	
Marking	UL	

accessories

installation	product code
mud ring 2-1/4"	9001-0003
mud ring adj. 2-1/4"	9001-0123
clt csc ring 2-1/4"	9001-0013
concrete ring + cap 2-1/4"	9001-0113

IC boxes	
IC box + plaster frame 3-1/2" high	9001-0101
IC box + plaster frame 2-1/4" high	9001-0103
bar hanger kit	9001-0102

luminaire output

	2700K				3000K			
	10°	20°	40°	60°	10°	20°	40°	60°
350mA (5.7W)	425lm	525lm	525lm	525lm	450lm	550lm	550lm	550lm
500mA (12.8W)	-	710lm	710lm	710lm	-	750lm	750lm	750lm

acrobat mini short

accessories

drivers (for remote installation or in IC box 3-1/2" high)	product code
SOLOdrive 0-10V 350mA 22W (1-2fx)	9000-1008
SOLOdrive 0-10V 500mA 22W (1-2fx)	9000-1002
SOLOdrive DALI 350mA 22W (1-2fx)	9000-1006
SOLOdrive DALI 500mA 22W (1-2fx)	9000-1001
Hatch phase dimming drive constant current 350mA - 12W (1fx)	9000-1003
Hatch phase dimming drive constant current 500mA - 12W (1fx)	9000-1004
<hr/>	
drivers (for remote installation only)	
Hatch phase dimming drive constant current 350mA - 30W (2-3fx)	9000-1010
Hatch phase dimming drive constant current 500mA - 30W (2-3fx)	9000-1011
