



installation

trim spot mini long

light specs

lamp	LED
optic	glass lens
driver	excluded
suitable for	damp locations
CRI	90+ 97
SDCM	SDCM2
class	class 2
drill hole size	1-5/8" (41mm)
recess height	3-1/2"
location	indoor
marking	UL (E543420)
	Title 24 JA8 Compliant

accessories

IC boxes	product code
IC box + plaster frame 3-1/2" high	9000-0101
bar hanger kit	9000-0102



trim spot mini long

luminaire output

	2700K				3000K			
	10°	20°	40°	60°	10°	20°	40°	60°
350mA (5.7W)	-	-	525lm	-	-	-	550lm	-
500mA (8.5W)	-	-	710lm	-	-	-	750lm	-

accessories

drivers (for remote installation or in IC box 3-1/2" high)	product code
SOLOdrive 0-10V 350mA 22W (1-2fx)	9000-1008
SOLOdrive 0-10V 500mA 22W (1-2fx)	9000-1002
SOLOdrive DALI 350mA 22W (1-2fx)	9000-1006
SOLOdrive DALI 500mA 22W (1-2fx)	9000-1001
Hatch phase dimming drive constant current 350mA - 12W (1fx)	9000-1003
Hatch phase dimming drive constant current 500mA - 12W (1fx)	9000-1004
drivers (for remote installation only)	
Hatch phase dimming drive constant current 350mA - 30W (2-3fx)	9000-1010
Hatch phase dimming drive constant current 500mA - 30W (2-3fx)	9000-1011