

driver matrix

constant current multipower

type	product code	dimming	cut-out	installation depth	forward voltage	current	max. watts	10° pc	20-60° pc	15-60° glass	10° outdoor	suitable for	dimensions	link
DALI / 0-10V dimmable driver 60W constant current multi power	9000-1014	DALI/0-10V/PUSH	remote	-	20-112V	350mA	39W	2-5 fx	2-5 fx	2-5 fx	-	dry locations	4-7/8 x 3 x 7/8"	↗
					2-112V	500mA	56W	-	2-5 fx	2-5 fx	-	dry locations	4-7/8 x 3 x 7/8"	↗
					2-86V	700mA	60W	-	-	2-4 fx	-	dry locations	4-7/8 x 3 x 7/8"	↗

deep dim

type	product code	dimming	cut-out	installation depth *	forward voltage	current	max. watts	10° pc	20-60° pc	15-60° glass	10° outdoor	suitable for	dimensions	link
SOLOdrive DALI 350mA 22W	9000-1006	DALI	plaster ring Ø2-1/4"	4-1/2"	2-42V	350mA	22W	1-2 fx	1-2 fx	1-2 fx	-	dry & damp locations	3-7/8 x 1-1/4 x 1"	↗
SOLOdrive DALI 500mA 22W	9000-1001	DALI	plaster ring Ø2-1/4"	4-1/2"	2-42V	500mA	22W	-	1-2 fx	1-2 fx	-	dry & damp locations	3-7/8 x 1-1/4 x 1"	↗
SOLOdrive DALI 700mA 22W	9000-1007	DALI	plaster ring Ø2-1/4"	4-1/2"	2-42V	700mA	22W	-	-	1 fx	-	dry & damp locations	3-7/8 x 1-1/4 x 1"	↗
SOLOdrive 0-10V 350mA 22W	9000-1008	0-10V	plaster ring Ø2-1/4"	4-1/2"	2-42V	350mA	22W	1-2 fx	1-2 fx	1-2 fx	-	dry & damp locations	3-7/8 x 1-1/4 x 1"	↗
SOLOdrive 0-10V 500mA 22W	9000-1002	0-10V	plaster ring Ø2-1/4"	4-1/2"	2-42V	500mA	22W	-	1-2 fx	1-2 fx	-	dry & damp locations	3-7/8 x 1-1/4 x 1"	↗
SOLOdrive 0-10V 700mA 22W	9000-1009	0-10V	plaster ring Ø2-1/4"	4-1/2"	2-42V	700mA	22W	-	-	1 fx	-	dry & damp locations	3-7/8 x 1-1/4 x 1"	↗

phase dimming

type	product code	dimming	cut-out	installation depth *	forward voltage	current	max. watts	10° pc	20-60° pc	15-60° glass	10° outdoor	suitable for	dimensions	link
Phase dimming / 0-10V dimmable driver constant current 350mA 15W	9000-1028	ELV/TRIAC/0-10V	plaster ring Ø2-1/4"	2-15/16"	15-42V	350mA	15W	1 fx	1 fx	1 fx	-	dry, damp & wet locations	2-2/3 x 1-9/16 x 7/8"	↗
Phase dimming / 0-10V dimmable driver constant current 500mA 15W	9000-1029	ELV/TRIAC/0-10V	plaster ring Ø2-1/4"	2-15/16"	14-30V	500mA	15W	-	1 fx	1 fx	-	dry, damp & wet locations	2-2/3 x 1-9/16 x 7/8"	↗
Phase dimming / 0-10V dimmable driver constant current 700mA 15W	9000-1030	ELV/TRIAC/0-10V	plaster ring Ø2-1/4"	2-15/16"	10-21V	700mA	15W	-	-	1 fx	-	dry, damp & wet locations	2-2/3 x 1-9/16 x 7/8"	↗

